

# Category 5e Toolless UTP Keystone Jack



KJ-1115-09

## Applications

Unshielded Toolless Cat5e Keystone Jack for B3 Internationals Faceplates, Surface mount Boxes and Snap-In Panels. Suitable for Local Area Networks, Data Centre and Video Applications delivering 1000base-t Gigabit Ethernet, 100BASE-TX Fast Ethernet, 622 Mbps ATM, 155 Mbps ATM and Composite Video.

## Product Picture



## Environmental Conditions

Relative Humidity (Operational)	Temperature	
	Storage	Operational
Maximum Non Condensing 93%	-40 to +70°C	-10 to +60°C

## Electrical Characteristics

Electrical Insulation Resistance	Dielectric Withstanding Voltage	Contact Resistance	
		Spring Wire	IDC
Min. 500 MΩ at 100Vd.c.	1000V RMS 60Hz for 1 minute	Max. 20mΩ	Max. 2.5mΩ

## Mechanical Characteristics

Retention	Insertion/Extraction Life	IDC Wire Gauge	Wiring Scheme
50N for 60s±5s	Min. 750 Cycles	22-24AWG	Labelled T568A & T568B

# Category 5e Toolless UTP Keystone Jack



KJ-1115-09

## Physical Characteristics

Housing	Spring Wire	IDC
High-Impact, Flame-Retardant Plastic	Phosphor Bronze Alloy plated with 50µ Inch of Gold	Phosphor Bronze Alloy with 100µ Inch of Sn Alloy

## Typical Performance Test Data

Frequency (MHz)	Min. Return Loss (dB)	Max. Insertion Loss (dB)	Min. NEXT (dB)
1	30.0	0.10	65.0
4	30.0	0.10	65.0
8	30.0	0.11	64.9
10	30.0	0.13	63.0
16	30.0	0.16	58.9
20	30.0	0.18	57.0
25	30.0	0.20	55.0
31.25	30.0	0.22	53.1
62.5	24.1	0.32	47.1
100	20.0	0.40	43.0

## Reference Standards

ISO/IEC 11801
ANSI/TIA/EIA-568-C2 5e Connecting Hardware
EN50173-1
UL94V-0
IEC 60603-7-5
UL1863
RoHS directives

## Ordering Information

Partnumber	Description
KJ-1115-09	Keystone jack CAT5e, UTP, 180 degree, White
KJ-1115-00	Keystone jack CAT5e, UTP, 180 degree, Black
KJ-1115-24	Keystone jack CAT5e, UTP, 180 degree, Yellow
KJ-1115-25	Keystone jack CAT5e, UTP, 180 degree, Green
KJ-1115-22	Keystone jack CAT5e, UTP, 180 degree, Red
KJ-1115-26	Keystone jack CAT5e, UTP, 180 degree, Blue

\*White is B3 International Standard Colour